

RVE Enhanced 2

CCW-RVE-214W-1S-30-WP-ENH2


Dedicated, enhanced performance specification at a competitive price.

Designed to handle a diverse range of fresh and frozen free flowing products, this weigher can be adapted to suit many packaging scenarios. Configured as a water proof design, the Enhanced 2 is built for long life operations in fresh or frozen applications achieving mid to high speeds for mid to high target weights.

- ▲ Specialised, versatile solution
- ▲ For fresh or frozen, free flowing product applications
- ▲ Mid to high speeds and excellent weighing yields
- ▲ Pre-configured for smart factories



Dimensions



Performance

	CCW-RVE-214W-1S-30-WP-ENH2	
Max. weighing speed*	100 WPM	
Max. vol. for weighing (per single dump)	4.5 litres	
Max piece length	130mm	
Weighing capacity setting (per head)	400g	800g
Minimum graduation	0.1g	0.2g
Machine target weight range	14 - 500g	25 - 1,000g

Specification

Touch screen display (RCU)	10.4" Colour LCD Display	
Number of presets	200	
Weigh cell	Ishida double-beam loadcell	
Materials	Product surfaces are made of stainless steel or other sanitary materials	
IP test rating	IP-66 Rating	
Power	Wattage	1.7KW
	Voltage	200-240V 50/60Hz 1-phase
Air**	110 litres/min (ANR) 0.01-0.02 Mpa Air hose - PT 3/8" (for air dryer connection)	
Net weight***	550kg	

Design and specifications are subject to change without notice (please confirm dimensions at point of order).

* Depends on product shape, product density, target weight, feeding conditions, etc.

** Compressed air supply is required only for WP machines. Note: Air hose compressor must be provided by user.

*** The machine weight varies depending on the options selected.



RVE Enhanced 2

Ishida has over 120 years history of weighing innovation, with more multihead weighers installed and adding value than any other supplier. The RVE series represents the latest in multihead weighing performance for speed, accuracy and reliability, and comes with a wide range of features to ensure high performance industrial weighing is achieved at an interesting price point.

Features & Benefits

Fast and precise weighing for improved productivity

High performance features include:

- ▲ Programmable 5 stage digital filtering
- ▲ Advanced automatic feeder adjustments
- ▲ High processing speed 10.4" web RCU

User-friendly design and easy set-up

Intuitive, easy-to-use RCU (Remote Control Unit)

- ▲ Simplifies initial set up and daily operations
- ▲ Minimises machinery downtime
- ▲ Maximises production efficiency
- ▲ USB data import/export with ethernet connectivity

Pre-configured for SMART FACTORIES

- ▲ Increased productivity with Industry 4.0
- ▲ Sentinel™ Reporting Pack included free of charge for life
- ▲ Provides instant visibility of live machine performance from anywhere in the world
- ▲ Optional access to remote technical support, rapid response diagnosis and pro-active performance monitoring

Compliance with FDA and EU Food Contact standards

All materials are FDA-approved and comply with Article 16(1) of Regulation (EC) No 1935/2004 and Article 15 of Regulation 10/2011. To fully meet the EU's Restriction of Hazardous Substances Directive (RoHS) non-hazardous materials are used for all circuit boards, parts, materials, and finishes.

Model	ENHANCED 2 - CCW-RVE-214W-1S-30-WP-ENH2
Contact parts finish	Hex embossed contact parts to promote free flow of semi-sticky product
Inlet chute	Adjustable frame and inner chute Lower section in blue metal detectable liner
Dispersion table	10° & 20° dispersion tables with skirt, cone type, vibratory
Ring gate	Included with blue metal detectable polyurethane fingers (controlling product infeed)
Radial feeder troughs	0° radial feeder troughs to increase control of product flow
Hoppers	Double opening hoppers
Discharge chutes	53° discharge chute for faster product flow with anti-swirl fins for increased product control Blue metal detectable cushion pipe
Timing hopper	6 litres capacity, pneumatically driven anti-leak timing hopper Options: Double opening, diverting or error diverting
Software	Multiple languages available, count priority, error signal output, auto zero cleaning mode, remote diagnostics software

*figures are based on historical application products and may vary depending on specific nature of product

ISHIDA EUROPE LIMITED
Kettles Wood Drive
Woodgate Business Park
Birmingham
B32 3DB
United Kingdom
Tel: +44 (0)121 607 7700
Fax: +44 (0)121 607 7888
info@ishidaeurope.com

ISHIDA CZECH REPUBLIC
Tel: +420 317 844 059
Fax: +420 317 844 052
info@ishidaeurope.cz

ISHIDA ROMANIA
Tel: +44 (0)121 607 7700
Fax: +44 (0)121 607 7888
info@ishidaeurope.ro

ISHIDA FRANCE
Tel: +33 (0)1 48 63 83 83
Fax: +33 (0)1 48 63 24 29
info@ishidaeurope.fr

ISHIDA RUSSIA AND CIS
Tel: +7 499 272 05 36
Fax: +7 499 272 05 37
info@ishidaeurope.ru

ISHIDA GERMANY
Tel: +49 (0)791 945 160
Fax: +49 (0)791 945 1699
info@ishida.de

ISHIDA SOUTH AFRICA
Tel: +27 (0)11 976 2010
Fax: +27 (0)11 976 2012
info@ishidaeurope.com

ISHIDA MIDDLE EAST
Tel: +971 (0)4 299 1933
Fax: +971 (0)4 299 1955
ishida@ishida.ae

ISHIDA SWITZERLAND
Tel: +41 (0)41 799 7999
Fax: +41 (0)41 790 3927
info@ishida.ch

ISHIDA NETHERLANDS
Tel: +31 (0)499 39 3675
Fax: +31 (0)499 39 1887
info@ishida.nl